

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number
WO 2004/039690 A1

(51) International Patent Classification⁷: **B65D 47/24**

(21) International Application Number:
PCT/NO2003/000361

(22) International Filing Date: 29 October 2003 (29.10.2003)

(25) Filing Language: Norwegian

(26) Publication Language: English

(30) Priority Data:
20025193 29 October 2002 (29.10.2002) NO

(71) Applicant and

(72) Inventor: N/ESJE, Kjell [NO/NO]; Askeveien 8, N-4314 Sandnes (NO).

(74) Agent: HÅMSØ PATENTBYRÅ ANS; Postboks 171, N-4302 Sandnes (NO)

CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, EG, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT (utility model), PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,

Published:
— with international search report

[Continued on next page]

(54) Title: AN OPENING-FORCE-MAXIMIZING DEVICE OF AN UNDERPRESSURE-ACTIVATED VALVE FOR A DRINKING CONTAINER



(57) **Abstract:** An opening-force-maximizing device of an underpressure-activated valve for a drinking container (2). The device includes a partition wall (6, 106, 206) enclosing an outlet opening (4) and being provided with a wall opening (8, 108, 208) in pressure-sealing contact with an axially movable valve sealing member (22, 122, 222) being in position of rest. It also includes a continuous membrane (12, 112, 212) being arranged to the container (2) and about a valve axis (14) through the wall opening (8, 108, 208). The membrane (12, 112, 212) has an axial extent and consists of an attachment end (12a, 112a, 212a) fixedly connected to the partition wall (6, 106, 206), and a movable manoeuvring end (12b, 112b, 212b) placed at an axial distance from the attachment end (12a, 112a, 212a). The manoeuvring end (12b, 112b, 212b) is arranged in a tensile-force-transmitting manner to said sealing member (22, 122, 222). By arranging the membrane (12, 112, 212) with a maximum longitudinal extent when at rest in its inactive position, and by being arranged radially flexible and deflectable and also being arranged in a manner inhibiting axial stretching, a maximum valve opening force is achieved when underpressure-activated.